

# 46000 Series Thermistor Components

Glass Hermetic Seal  
 2252 Ohm to 30K Ohm Resistance  
 @ 25°C  
 0.125" (3.2 mm) Maximum  
 Diameter  
 Interchangeability to  $\pm 0.05^\circ\text{C}$   
 Excellent High Temperature  
 Performance  
 Excellent Long Term Stability  
 RoHS Compliance



## 46000 SERIES THERMISTORS

Hermetically Sealed Glass Encapsulated Precision Interchangeable NTC Thermistor utilizing high stability pressed-disk ceramic sensor for high temperature and high stability applications

### FEATURES

- Glass Hermetic Seal
- 2252 Ohm to 30K Ohm Resistance @ 25°C
- Interchangeability to  $\pm 0.05^\circ\text{C}$
- Excellent High Temperature Performance
- Drift Certified Unmatched Long Term Stability
- High Sensitivity
- RoHS Compliance

### APPLICATIONS

- High Moisture Applications
- Low to Mid Range Temperature Applications
- Tight Tolerance Instrumentation
- Use up to 250°C
- Applications Requiring Outstanding Stability and/or Requiring Sensing Small Changes in Temperature
- Allows use in Applications World-wide

## Stability

**Typical Thermometric Drift**, after continuous exposure at listed operating temperatures.

Operating Temperature	10 months	100 months
25°C	< 0.01°C	< 0.01°C
70°C	< 0.01°C	< 0.01°C
100°C	0.02°C	0.03°C
150°C	0.05°C	0.08°C
200°C	0.22°C	0.60°C

# 46000 Series Thermistor Components

## product definition

	Part Number	Zero Power Resistance Ohm at 25°C	Beta 0- 50°C (K)	Ratio Ohm 25/125°C	Maximum Working Temperature
<b>±0.2°C Interchange- ability Tolerance 0 – 70°C</b>	<a href="#">46004</a>	2252	3891	29.26	200°C
	<a href="#">46005</a>	3000	3891	29.26	200°C
	<a href="#">46007</a>	5000	3891	29.26	200°C
	<a href="#">46017</a>	6000	3891	29.26	200°C
	<a href="#">46016</a>	10K	3891	29.26	200°C
	<a href="#">46006</a>	10K	3574	23.51	200°C
	<a href="#">46008</a>	30K	3810	29.15	200°C
	<b>±0.1°C Interchange- ability Tolerance 0 – 70°C</b>	<a href="#">46033</a>	2252	3891	29.26
<a href="#">46030</a>		3000	3891	29.26	200°C
<a href="#">46034</a>		5000	3891	29.26	200°C
<a href="#">46037</a>		6000	3891	29.26	200°C
<a href="#">46036</a>		10K	3891	29.26	200°C
<a href="#">46031</a>		10K	3574	23.51	200°C
<a href="#">46032</a>		30K	3810	29.15	200°C

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

## Ordering Information

### NORTH AMERICA

Measurement Specialties, Inc.  
910 Turnpike Road  
Shrewsbury, MA 01545  
Tel: 1-508-842-0516  
Fax: 1-508-842-0342

### EUROPE

Measurement Specialties, Inc  
Ballybrit Business Park  
Galway, Ireland  
Tel: +353-91-753238  
Fax: +353-91-770789

### ASIA

Measurement Specialties (China) Ltd.  
No. 26 Langshan Road  
Shenzhen High-Tech Park (North)  
Nanshan District, Shenzhen 51807  
China  
Tel: +86 (0) 755 33305088  
Fax: +86 (0) 755 33305099  
Sales email: [temperature.sales.asia@meas-spec.com](mailto:temperature.sales.asia@meas-spec.com)

Sales email:  
[temperature.sales.amer@meas-spec.com](mailto:temperature.sales.amer@meas-spec.com)

Sales email:  
[temperature.sales.emea@meas-spec.com](mailto:temperature.sales.emea@meas-spec.com)